

| Specifications | | ADVANCED JET | | SOLJET PRO III | |
|-------------------------------------|---------------------|---|--|---|--|
| | | AJ-1000i | AJ-740i | XJ-740 | XJ-640 |
| Printing technology | | Piezoelectric inkjet | | Piezoelectric inkjet | |
| | Width | 1220 to 2641 mm (48 to 104 in.) | | 210 to 1879 mm (8.3 to 74 in.) | 210 to 1625 mm (8.3 to 64 in.) |
| Media | Thickness | Maximum 1.0 mm (39 mil) with liner | | Maximum 1.0 mm (39 mil) with liner | |
| | Roll outer diameter | Maximum 250 mm (9.8 in.) | | Maximum 210 mm (8.3 in.) | |
| | Roll weight | Maximum 100 kg (220 lb.) | | Maximum 47 kg (103 lb.) | Maximum 40 kg (88 lb.) |
| | Core diameter | 76.2 mm (3 in.) | | 76.2 mm (3 in.) or 50.8 mm (2 in.) | |
| Printing width | | Maximum 2600 mm (102.3 in.) | Maximum 1870 mm (73.6 in.) | Maximum 1869 mm (73.6 in.) *1 | Maximum 1615 mm (63.6 in.) *1 |
| Ink cartridges | Types | Exclusive Roland EcoXtreme i or EcoXtreme LT cartridge | | Exclusive Roland ECO-SOL MAX cartridge | |
| | Capacity | 1 liter | | 220 cc or 440 cc | |
| | Colors | 6 colors (cyan, magenta, yellow, black, light cyan, and light magenta) | | 6 colors (cyan, magenta, yellow, black, light cyan, and light magenta) or 4 colors (cyan, magenta, yellow, and black) | |
| Printing resolution (dots per inch) | | Maximum 720 dpi | | Maximum 1440 dpi | |
| Distance accuracy | | Error of less than ±0.3 % of distance traveled, or ±0.3 mm, whichever is greater *2 | | Error of less than ±0.3 % of distance traveled, or ±0.3 mm, whichever is greater *3 | |
| Media heating system *4 | | Preheater and print heater, setting range for the preset temperature: 35 to 60°C (95 to 140°F) Heating method (Used in combination with the blower fan). setting range for the preset temperature: 35 to 60°C (95 to 140°F) | | Print heater, setting range for the preset temperature: 30 to 50°C (86 to 122°F) Dryer, setting range for the preset temperature: 30 to 55°C (86 to 130°F) | |
| Media take-up system | Roll outer diameter | Maximum 250 mm (9.8 in.) | | Maximum 250 mm (9.8 in.) | |
| | Roll weight | Maximum 100 kg (220 lb.) | | Maximum 50 kg (110 lb.) | |
| Connectivity | | Ethernet (10BASE-T/100BASE-TX, automatic switching) | | Ethernet (10BASE-T/100BASE-TX, automatic switching) | |
| Power-saving function | | Automatic sleep | | Automatic sleep | |
| Power requirements | | Printer: AC 200 to 240 V ±10 %, 10 A, 50/60 Hz Dryer: AC 200 to 240 V ±10 %, 10 A, 50/60 Hz | Printer: AC 200 to 240 V ±10 %, 8.5 A, 50/60 Hz Dryer: AC 200 to 240 V ±10 %, 8.5 A, 50/60 Hz | AC 100 to 120 V ±10 %, 13 A, 50/60 Hz or AC 220 to 240 V ±10 %, 7 A, 50/60 Hz | |
| Power consumption | During operation | Printer: Approx. 1600 W, Dryer: Approx. 2300 W | | Approx. 1600 W | |
| | Sleep mode | Approx. 60 W | | Approx. 47 W | |
| Acoustic noise level | During operation | 70 dB (A) or less | | 64 dB (A) or less | |
| | During standby | 40 dB (A) or less | | 45 dB (A) or less | |
| Dimensions (with stand) | | 4299 (W) x 1115 (D) x 1413 (H) mm (169.3 (W) x 43.9 (D) x 55.7 (H) in.) | 3632 (W) x 1115 (D) x 1359 (H) mm (143 (W) x 43.9 (D) x 53.5 (H) in.) | 3169 (W) x 1103 (D) x 1260 (H) mm (124.8 (W) x 43.4 (D) x 49.6 (H) in.) | 2948 (W) x 1103 (D) x 1260 (H) mm (116 (W) x 43.4 (D) x 49.6 (H) in.) |
| Weight (with stand) | | 598 kg (1319 lb.) | 478 kg (1050 lb.) | 225 kg (495 lb.) | 213 kg (469 lb.) |
| Environmental | Power on | Temperature: 20 to 32°C (68 to 90°F) humidity: 35 to 80 % (no condensation) | | Temperature: 15 to 32°C (59 to 90°F) (20°C [68°F] or more recommended), humidity: 35 to 80 %RH (non-condensing) | |
| | Power off | Temperature: 5 to 40°C (41 to 104°F), humidity: 20 to 80 % (no condensation) | | Temperature: 5 to 40°C (41 to 104°F), humidity: 20 to 80 %RH (non-condensing) | |
| Accessories | | Power cords, roll shafts, end caps, spacers, media reinforcement pipe, paper tube, drain bottle, media gauge, media clamps, hexagonal wrenches, Head-unit tool, cleaning kit, syringe, tube, maintenance liquid cartridge, software RIP, Roland-PrintServer CD-ROM, User's Manual, Setup Guide, Roland-PrintServer Network Settings Guide | | Stand, power cord, media clamps, media flanges, replacement blade for separating knife, cleaning kit, software RIP, and User's Manual, etc. | |

*1 The length of printing is subject to the limitations of the program.
*2 At Roland PET film, print travel: 1 m, temperature: 20°C (68°F), humidity: 50 %, not assured when the print heater or dryer is used.
*3 At Roland PET film, print travel: 1 m, temperature: 25°C (77°F), humidity: 50 %, not assured when the print heater or dryer is used.
*4 Warm-up is required after power-on. This may require 5 to 20 minutes, depending on the operating environment. Depending on the ambient temperature and media width, it may not reach a preset temperature.

| Roland VersaWorks System Requirements | |
|---------------------------------------|--|
| Operating system | Windows Vista® Ultimate Service Pack 1 or Business Service Pack 1 (32-bit edition), Windows Vista® Ultimate or Business (32-bit edition), or Windows® XP Professional Service Pack 2 or 3, or Windows® 2000 Service Pack 4 |
| CPU | 2.0 GHz or faster Pentium 4 recommended |
| RAM | 1 GB or more recommended (Windows Vista®: 2 GB or more recommended) |
| Video card and monitor | A resolution of 1280 x 1024 or more recommended |
| Free hard-disk space | 40 GB or more recommended |
| Optical drive | DVD-ROM drive |

| Options for Advanced JET AJ-1000i/AJ-740i | |
|---|-------------------------------|
| Mesh Printing Unit | MU-1000 For AJ-1000i |
| | MU-740 For AJ-740i |
| EcoXtreme i Ink | AI3-MG Magenta, 1000 cc |
| | AI3-YE Yellow, 1000 cc |
| | AI3-CY Cyan, 1000 cc |
| | AI3-BK Black, 1000 cc |
| | AI3-LC Light cyan, 1000 cc |
| | AI3-LM Light magenta, 1000 cc |
| EcoXtreme LT Ink | AI2-MG Magenta, 1000 cc |
| | AI2-YE Yellow, 1000 cc |
| | AI2-CY Cyan, 1000 cc |
| | AI2-BK Black, 1000 cc |
| | AI2-LC Light cyan, 1000 cc |
| | AI2-LM Light magenta, 1000 cc |
| Cleaning liquid | AI-CL 1 pc, 1000 cc |
| Maintenance liquid | AI-ML 1 pc, 500 cc |

| Options for SOLJET PRO III XJ-740/XJ-640 | | |
|--|-----------------|---|
| ECO-SOL MEDIA | SPVCB-1270 | PVC banner, 1270 mm x 20 m (50' x 65ft) |
| | SP-M-1270 | Matte PET film, 1270 mm x 30 m (50' x 98ft) |
| | SFPLF-1300 | Backlit film, 1300 mm x 30 m (51' x 98ft) |
| | SP-SG-1270G | PET semi gloss, gray adhesive, 1270 mm x 30 m (50' x 98ft) |
| | SP-SG-1270TR | PET semi gloss, removable adhesive, 1270 mm x 30 m (50' x 98ft) |
| | SCM-GPPG-40-127 | White glossy photo paper, 1270 mm x 40 m (50' x 131ft) |
| | SCM-GPPM-40-127 | Photo matte paper, 1270 mm x 40 m (50' x 131ft) |
| | SCM-GVWG-40-137 | Calendered white vinyl, adhesive, 1370 mm x 40 m (53' x 131ft) |
| | SV-G-1270G | Gray adhesive vinyl, 1270 mm x 30 m (50' x 98ft) |
| | ESP-CL-1300 | Clear PET film, 1300 mm x 30 m (51' x 98ft) |
| ECO-SOL MAX Ink | SP-CL-1000T | Clear PET film, adhesive, 1000 mm x 20 m (39' x 65ft) |
| | ESL3-4MG | Magenta, 440 cc |
| | ESL3-4YE | Yellow, 440 cc |
| | ESL3-4CY | Cyan, 440 cc |
| | ESL3-4BK | Black, 440 cc |
| | ESL3-4LC | Light cyan, 440 cc |
| | ESL3-4LM | Light magenta, 440 cc |
| | ESL3-MG | Magenta, 220 cc |
| | ESL3-YE | Yellow, 220 cc |
| | ESL3-CY | Cyan, 220 cc |
| Cleaning liquid | ESL3-BK | Black, 220 cc |
| | ESL3-LC | Light cyan, 220 cc |
| | ESL3-LM | Light magenta, 220 cc |
| | SL-CL | 1 pc, 220 cc |
| Heater and blower | DU-740 | For XJ-740 |
| | DU-640 | For XJ-640 |

Roland DG products that feature this environmental label meet the company's criteria for environmental consciousness, a set of standards based on ISO 14021 self-declaration type II. For more information, please visit www.rolanddg.com.



ISO 14001:2004 and ISO 9001:2008 Certified
Roland pursues both environmental protection and continuous quality improvement. Under the philosophy of preserving the environment and human health, Roland is actively working to abolish organic solvents in production, to reduce and recycle waste, to reduce power use, and to purchase recycled products. Roland constantly strives to provide the most highly reliable products available.




Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. Adobe, PostScript, PostScript 3 and the PostScript logo are trademarks of Adobe Systems Incorporated. All other trademarks are the property of their respective owners. Roland DG Corp. has licensed the MMP technology from the TPL Group.





Powerful Performance With Rich, Vivid Color



- 1 Dynamic, durable billboards
- 2 High-density images on flexible face media
- 3 Spectacular fleet graphics and wraps
- 4 Exquisite custom retail decor
- 5 Exceptional soft signage for easy, effective event promotion
- 6 Rich, dense colors for superior tradeshow exhibits
- 7 Corporate advertising with impact
- 8 Stunning window displays

- 1 Photorealistic skin tones
- 2 Flawless fine art giclees
- 3 Custom wall coverings
- 4 High-impact event posters
- 5 Beautiful outdoor banners
- 6 Vivid color backlits
- 7 Bold, colorful POP displays
- 8 Durable outdoor signs

Exceptional Speed and Image Quality

The SOLJET PRO III XJ series is offered in 64" and 74" models, combining high-speed performance and superior image quality for the ultimate in six- or four-color digital printing.



SOLJET PRO III


XJ-740/XJ-640

Optimum Productivity and Low Running Costs

Available in 64" and 74" models, the six-color (CMYKLcLm) or four-color (CCMMYK) XJ series builds on Roland's renowned SOLJET technology to achieve exceptional image quality at higher print speeds. With a maximum print speed of 42.6m²/hr (458.61sqft/hr), the XJ is designed for production printing of indoor and outdoor graphics including banners, signs, point of purchase displays, vehicle graphics, backlit displays, event graphics and more. The XJ series supports a wide variety of media including vinyl, banner, photo paper, poster paper and canvas. For even greater productivity, the XJ features an automated maintenance system that saves valuable ink and time, resulting in lower overall running costs. The XJ's in-line print head configuration eliminates the need for lengthy calibration procedures as well.

Outstanding Visual Impact

The XJ series prints at up to 1440 x 1440 dpi resolution in dense, rich colors for indoor and outdoor graphics that look great up close and at a distance. Thanks to Roland Intelligent Pass Control technology, the XJ has been optimized to achieve unparalleled image quality in every print mode and produces flawless skin tones, high-contrast images, and solid colors with no traces of banding even at the highest print speeds. A built-in tri-heater system increases media receptiveness for maximum ink brightness and fastness.




Exceptional Print Quality with ECO-SOL MAX Ink

ECO-SOL MAX eco-solvent ink delivers high color density and a wide gamut for exceptional images print after print. ECO-SOL MAX performs on a wide range of both coated and uncoated media, including backlit film, for increased versatility. Fast-drying and scratch-resistant, ECO-SOL MAX produces prints that dry quickly for easy handling throughout the production and finishing processes. Packaged in no-mess 220 and 440 cc cartridges, ECO-SOL MAX is virtually odorless for maximum convenience and comfort.



Added Features for Maximum Performance

The XJ series offers numerous advanced features for high-volume printing. Rigid construction and a heavy-duty take-up system support large media rolls weighing up to 47kg (103.6lbs). Easy access media shafts make it convenient to load even the heaviest media. Additional system enhancements include improved pinch rollers, grit rollers and additional grit power for flawless media feeding and tracking. Extended built-in media edge clamps prevent media curling and ragged edges. Media flanges are included as well for precision media tracking through long unattended production runs. A high-speed network board supports rapid data transfers, and an optional dryer/blower unit further expedites the production process.



Powerful VersaWorks RIP Software

Included in both the AJ-i and XJ series, Roland VersaWorks RIP was written from the ground up to be easy to use while offering advanced features including the Max Impact color management preset, the Roland Color System for precision spot color matching, and Variable Data Printing for custom prints with variable data.



Default preset features fine gradations for close-up viewing.



Max Impact provides vivid colors for outdoor signs.

The Max Impact preset produces deeper, more vivid blues and reds, the fundamental colors for outdoor graphics, while preserving the overall color balance required for beautiful, photorealistic images. Or you can choose the default preset to faithfully reproduce human skin tones, pastel as well as natural colors, and metallic surfaces with superb gradations. Built on an Adobe Postscript engine, VersaWorks includes a wide variety of convenient layout, edit and print functions, and allows users to import files from popular design programs and preview jobs on screen. VersaWorks also includes more than 150 ICC profiles for reliable results the first time and every time. The Roland@NET automated update feature ensures ongoing access to the latest VersaWorks version and profiles available.



74" XJ-740
● 74" 6-color CMYKLcLm or 4-color CCMMYK wide-format inkjet printer

64" XJ-640
● 64" 6-color CMYKLcLm or 4-color CCMMYK wide-format inkjet printer



High-Speed Performance

Designed for high-volume printing and rush jobs, the AJ-i produces billboards, banners, backlit, fleet and vehicle graphics, and point of purchase displays at a maximum print speed of up to 90 m²/hr (968 sqft/hr). With 72 mm-wide heads, 510 nozzles per line and 35 pl per dot, the AJ-i offers superior image quality at 45 m²/hr (484 sqft/hr). With Roland Intelligent Pass Control, the AJ-i achieves up to 25 %* higher productivity for banner printing in standard print mode. For example, the AJ-i can print five rolls of banner measuring 2.5 m (8.2') wide by 50 m (164') long in standard print mode (bi-direction) in the same time it took the previous model to print just four rolls. Additional performance features, including a heavy-duty tension-controlled take-up system for rolls weighing up to 100 kg (220 lbs), make the AJ-i ideal for long production runs and unattended printing. A powerful drying system quickly dries ink and media for high-speed applications.

*Increased to 20 m²/hr (215.31sqft/hr) from 16 m²/hr (172.25 sqft/hr) for unidirection, and to 30 m²/hr (322.97 sqft/hr) from 24 m²/hr (258.37 sqft/hr) for bi-direction.



Superior Image Quality

The addition of Roland Intelligent Pass Control allows the AJ-i to produce sharp, vivid and solid images with smoother gradations and virtually no banding. With a maximum print resolution of 720 x 720 dpi, the AJ-i series produces brilliant six-color CMYKLCm graphics with superior outdoor graphics. In addition, feed calibration can be adjusted immediately at any time during the printing process to reduce media waste. The AJ-i's high-density inks image well even on flexible face media, and top quality on both glossy and matte vinyl.



Brilliant, Durable EcoXtreme Inks

Exclusively for the AdvancedJET AJ-i series, the latest Roland EcoXtreme i ink provides outstanding color density, wide gamut and rugged durability while dramatically reducing odor. Choose from two formulations — EcoXtreme i for durability of up to three years outdoors, and EcoXtreme LT for more cost-effective, short-term applications. Both EcoXtreme ink sets are available in

six colors (CMYKLCm). EcoXtreme inks offer exceptional bonding with uncoated banner substrates and tarpaulin, as well as enhanced scratch and alcohol resistance for outstanding outdoor durability.




Minimum Maintenance and Ownership Costs

The price and installation costs of many wide and grand-format printers can run as high as the price of an expensive house or yacht. By comparison, an AJ-i can be purchased and installed for a fraction of this cost. Operational costs for the AJ-i are lower as well due to an innovative automated intelligent maintenance system that saves ink and reduces down time. This advanced system performs routine maintenance tasks automatically, eliminating the need for time-consuming daily manual cleanings. The AJ-i's intelligent maintenance system even adjusts the maintenance schedule automatically depending on the room temperature. As a result, manual cleaning around the print head and capping station is required only every two weeks.

Convenient Optional Mesh Printing Unit


The AJ-i's versatility can be further enhanced with the optional MU Mesh Printing Unit for economical unlined mesh media. Custom engineered for the AJ-i, the MU is easy to attach and detach and features a built-in drainage system for easy removal of excess ink. Popular for a variety of indoor and outdoor applications, mesh is particularly well suited for graphics that may be exposed to excessive wind or any graphic calling for a unique sheer look. Unlined mesh offers many advantages over lined mesh. Unlined mesh is less expensive per square meter, easier to print, handle and transport, and produces no liner waste.



Print on Banner Media



Quickly and Easily Attach Mesh Printing Unit



Print on Mesh

Maximum Productivity

The AdvancedJET AJ-i grand format line is ideal for high-volume production printing in excellent quality with innovative Roland Intelligent Pass Control. Available in 104" and 74" models, the six-color AdvancedJET AJ-i delivers maximum productivity with world-class Roland engineering.



- 104" AJ-1000i**
● 104" 6-color CMYKLCm industrial high-speed inkjet printer
- 74" AJ-740i**
● 74" 6-color CMYKLCm industrial high-speed inkjet printer



ADVANCED JET AJ-1000i/AJ-740i